Holtam Metal Fabrication 7435 Les Hughes Road Fairview, TN 37062 615-799-9188 email: rjholtam@worldnet.att.net

DAKAR CENTER STAND:

- powder coated steel construction
- adjustable limits Two bolts allow you to set the angle of the stand in the down position (to adjust the stability of the bike on the stand), and two more bolts allow you to set the angle of the stand in the up position (to enable sufficient ground and lean-angle clearance). Once you have set the adjustment bolts to your preference, there is a hex screw that you tighten up against each adjustment bolt to lock in your settings.
- accommodates a larger rear tire The cross brace is welded closer to the pivot bolts to allow clearance for a larger rear tire.
- larger step pad with traction bumps The pad mounted to the step lever is slightly enlarged for comfort and convenience. The pad also has four spot-welds to help prevent your boot from slipping.
- all hardware and a spring-stretching tool is included The stand comes with two stainless steel springs, two stainless steel sleeves and two zinc-plated bolts with washers and a self-locking nuts. A simple, but effective, spring-stretching tool enables easy installation of the springs.

OPTIONAL BASH PLATE:

- 1/8-inch aluminum construction with a brushed finish
- mounts securely The bash plate mounts with the center stand bolts to the frame. Two rubber coated strap clamps secure the lower portion to the legs of the center stand.
- fits F650GS center stands, including those that have been lengthened to fit the Dakar
- all hardware and spring-stretching tool included If

purchased separately (example: for an F650GS), two bolts with washers and self-locking nuts are provided and since your stand will have to be removed to install the bash plate, the springstretching tool is also provided.



